



Hydraulic Crimp Heads



OP-60S

Accepts existing 60ton U-type dies
 Max connector outer diameter: Approx. 60mm
 Ram stroke: 38.5 mm
 Oil volume required: 303 cc
 Force at die face: 60 TON (Single, Double Acting)
 Size: 1.46 (Dia)x450(H)mm
 Weight: 22.0kg



OP-100W

Max connector outer diameter: Approx. 75mm
 100 ton class compression head
 Ram stroke: 22mm
 Oil volume required: 314 cc
 Output force: 100 TON (Double Acting)
 Size: 200 (Dia)x350(H)mm
 Weight: 32.0kg



OP-200W

Max connector outer diameter: Approx. 90mm
 100 ton class compression head
 Ram stroke: 40mm
 Oil volume required: 1134 cc
 Output force: 200 TON (Double Acting)
 Size: 270 (Dia)x415(H)mm
 Weight: 84kg



OP-60H

FOR DISTRIBUTION AND TRANSMISSION
 Lines up to 1000mm²
 Output force: 60 TON (Single Acting)
 Size: 146 (Dia)x450(H)mm
 Weight: 22.0kg
 WITH STANDARD DIES: 500,630,800,1000mm²



WEB: www.austutilities.com.au
 EMAIL: sales@austutilities.com.au

PHONE: 08 9406 3200