



# Insulated Torque Screwdriver



## Torque Vario-S VDE torque screwdriver

Insulation up to 1,000 V AC, GS-mark.  
Torque valve can be set via window  
Scale Automatic release

Order No.	Nm				
26626	1,0-5,0	6%	3,8	138	36

## Overview / Features

**Handle:** Torque infinitely adjustable with Torque-Setter setting tool (also supplied). Ergonomic multi-component handle, insulation up to 1,000 V AC, GS mark.

Handle sizes proportioned to optimise torque setting. Audible and perceptible click when the pre-test has been attained. { %s }

**Standards:** Manufactured ass. To IEC 60900:2012. EN ISO 6798, BS EN 26789, ASME B107.14M

**Accuracy:** 6% traceable to national standards.

**Holder:** SlimTorque bit holder (included in delivery) for 6 mm slimBits.

**Application:** For controlled fastening on live parts up to 1,000 V AC, for use only in combination with a slimTorque VDE bit holder for 6 mm slimBits.

**Extra:** Delivered in practical box, incl. factory calibration certificate.



**WEB:** [www.austutilities.com.au](http://www.austutilities.com.au)  
**EMAIL:** [sales@austutilities.com.au](mailto:sales@austutilities.com.au)

**PHONE:** 08 9406 3200