



Pole Chainsaw

CS28 & CS25

The CS25 and CS28 Pole chain Saws are ideal for use by right of way crews, utilities, parks departments and grounds-keepers. Lightweight, they feature fibreglass poles for convenient handling in tight spots and automatic chain oiling for long, reliable service.

The CS28 is designed for HTMA Type II circuits and has an optimum flow of 8gpm/30 lpm. The CS25 is ideal for HTMA Type I circuits commonly found on bucket trucks where hydraulic circuit flow is often limited to 4-6 gpm/15-23 lpm. For greater versatility, the Stanley "Dual Spool" permits the user to adjust the saw to operate from either open or closed-centre circuits.

SPECIFICATIONS

SPECIFICATIONS				
	CS28		CS25	
ITEM	U.S.A	METRIC	U.S.A	METRIC
Cut Capacity	13in	33cm	13in	33cm
Weight *	10.4 & 11lb	4.7 & 5kg	10.4 & 11lb	4.7 & 5kg
Overall Length **	75 & 90in	190 & 230cm	75 & 90in	190 & 230cm
Pressure	1000-2000 psi	70-140 bar	1000-2000 psi	70-140 bar
Flow Range	7-9 gpm	26-34 lpm	4-6 gpm	15-23 lpm
Optimum Flow	8 gpm	30 lpm	5 gpm	20 lpm
Porting	-8SAE		-8SAE	
Connect Size/Type	3/8 NPT Male Adaptor			
* Weight includes bar and chain but not quick couplers.				
** Length includes bar and chain but not quick couplers.				

Features	Benefits
Pole Centre Line Close to Bar Centreline	Reduced operator Fatigue
External Bar Oiler	Quick/Convenient Adjustments
Common Bar and Chain	Easy to Source Replacement parts
OCC/CC Dual spool	Match the tool hydraulics to the circuit
Integral Branch hook	Extra long bucking face/brush management
Meets ASTM F711-83	Passes requirements for live-line tools
Rim Sprocket	Smoother Operation, retains chain
Guide Plates	Keeps loose chain in place



WEB: www.austutilities.com.au
EMAIL: sales@austutilities.com.au

PHONE: 08 9406 3200