LCS800 & LCS850
Unistar Command Centre

Made in the USA

Features

The Unistar Command Centre combines a full feature 200 Watt siren, an 8-function light control switch panel, and a traffic director controller (LCS850 only) all into one dual colour keypad driven unit.

The control head features a dual colour (Red & Green) lighted keypad, a 4-position progressive slide switch with LED indicators, LED speaker diagnostics, an attached noise cancelling PA microphone and are available with or without a flush mounting flange.

Selectable Operating modes are wail, yelp, hands free, phaser, manual, alert and radio. Operating tones are wail, yelp, air horn, phaser, manual, and two-tone. Positive and negative switching for AUX and Park Kill Inputs.

The Unistar Command Centre is protected against speaker shorts with a self-resetting circuit and a high and low voltage shutdown feature. These unites also feature integrated horn ring transfer output, jumpers for option selections, public address override and separate volume control for the radio repeat and public address functions. The amplifier and switch box mount conveniently and connects to the control head through a telephone style cable.

Ships complete with wire harness with positive locking connector, mic clip, mounting bracket, hardware, 30 standard function labels, and instructions.

Specifications

- Voltage: 10-16VDC
- Output: 100/200 watts
- Frequency: 675-1633Hz
- Amplifier size: 65mmH x 178mmW x 190mmD
- Control head size: 85mmH x 170mmW x 20mmD
- Amp Draw: 8 amps per speaker
- LED speaker diagnostics
- Self resetting circuit protection against speaker shorts
- Integrated public address microphone
- Eight light functions
- Replaceable jumpers for option selection

- Dual colour backlighting on keyboard (Amber/Red)
- Four position progressive slide switch with LED indicators
- Park kill input
- Auxiliary input
- Positive locking wiring harness included
- Universal mounting bracket or flange mount available
- Truck mount amplifier
- High and low voltage shutdown protection
- 30 standard function replaceable labels
- Drives one or two 100 watt speakers