

YANMAR Generator Sets

YDG Generators

Air Cooled Diesel Generators - Single Phase



Features and benefits

- Genuine quality and reliability
- ♦ Low oil shutdown
- Voltage meter
- Automatic voltage regulation (AVR)
- ◆ 12volt-83 amp simultaneous battery charging capability
- Battery cables and battery included on electric start models
- Visual fuel level gauge located on tank
- Low vibration utilising isolation mounts between engine/alternator assembly and frame
- ♦ Full roll frame protection

MODEL	YDG2700N		YDG3700N		YDG5500N
MAX. Output kVa	2	.2	3	2	4.6
Cont, Output kVa		2		3	4.2
DC Output	12 Volt - 8.3amp				
Voltage	240				
Power Outlets	15 amp - x 2 GPO				
Frequency (Hz)	50				
Speed (rpm)	3000				
Voltage Reg	AVR				
AC Switch	All Models				
DC Breaker	All Models				
Engine Model	L48N5-G(E)Y		L70N5-G(E)Y		L100N5-GEYT
Fuel Tank Cap (I)	7.2		13		13
Fuel consumption (L/HR) @ 75% load	1.02		1.36		1.85
Noise Level at 7m dB (A) @ 100% load	79		81		85
Engine Type	4-Stroke, Air Cooled Diesel Engine				
Starting System	Recoil	Recoil/ Electric	Recoil	Recoil/ Electric	Recoil/Electric
Dimensions (LxWxH)	590x416x500	649x416x500	650x496x530		720x480x578
Dry Weight (kg)	55	64	70	82	95



WEB: www.austutilities.com.au EMAIL: sales@austutilities.com.au

PHONE: 08 9406 3200