



Adjustable Wrenches



Industrial Phosphate Finish Adjustable Wrenches

Features Precision Scale Opening with Metric Graduations
 New phosphate finish improves the rust resistance over black oxide finishes, resulting in a hard and good abrasion finished surface.
 Specifications: Drop forged, heavy-duty rack and worm adjustment, 22.5 degree angle head. Material Aisi-6140 Alloy steel.
 Hardness 50 HRC US. Federal Specification: GGG-W-631B, ANSI, DIN 3117(GS Approved No. 77/94)

Part No.	Length	Max. Opening	Opening mm	Weight
10004	4"(100mm)	1/2"	13mm	55g
10006	6"(150mm)	3/4"	19mm	125g
10008	8"(200mm)	15/16"	24mm	255g
10010	10"(250mm)	1.18"	29mm	420g
10012	12"(300mm)	1.516"	34mm	660g
10015	15"(380mm)	1.34"	43mm	1210g
10018	18"(450mm)	2.116"	53mm	2020g
10024	24"(600mm)	2.716"	62mm	3450g



Super-Satin Aero Finish Adjustable Wrenches

Precision Scale Opening with Metric Graduations
 Super-Satin is a special patented no shine and perfectly all smooth surface developed for the aeronautical service industry.
 Specifications: Drop forged, heavy-duty rack and worm adjustment, 22.5 degree angle head. Material Aisi-6140 Alloy steel.
 Hardness 50 HRC US Federal Specification: GGG-W-631B, ANSI, DIN 3117(GS Approved No. 77/94)

Part No.	Length"	Max. Opening	Opening mm	Weight
10204	4"(100mm)	1/2"	13mm	55g
10206	6"(150mm)	3/4"	19mm	125g
10208	8"(200mm)	15/16"	24mm	255g
10210	10"(250mm)	1.18"	29mm	420g
10212	12"(300mm)	1.516"	34mm	660g
10215	15"(380mm)	1.34"	43mm	1210g
10218	18"(450mm)	2.116"	53mm	2020g
10224	24"(600mm)	2.716"	62mm	3450g



Specialty Adjustable Wrenches

10808 8" Super Thin Adjustable Wrench

Super thin head allows use in limited and narrow spaces. Extra wide jaw opening up to 38mm. Features deep throat jaw depth which is 30% greater than standard wrenches.
 Capacity: 1.1/2"(38mm)
 Length: 8"(200mm)

10312 12" Adjustable Hammer Wrench

Precision Scale Opening with Metric Graduations
 Heavy-duty 12" adjustable wrench with special anvil built-in to the head enabling the wrench to be used as a hammer. Industrial phosphate finish.
 Capacity: 1.12"(38mm)
 Length: 12"(300mm)

32490 15" Adjustable Construction Wrench

Head is 15° offset. Tang is wedged into the mating holes. Flat area between tang and head allows the tool to be hung from a belt without turning in the holder.
 Capacity: 1.13/16"(46mm)
 Length: 15"(380mm)



WEB: www.austutilities.com.au
 EMAIL: sales@austutilities.com.au

PHONE: 08 9406 3200