



Sonel 1kV Insulation Resistance Meters



**Part Numbers:
MIC-10 & MIC-30**



- ◆ **Insulation resistance measurement:**
 - Selected test voltage: 50, 100, 250, 500, 1000v (MIC-10) or any voltage in the 50...1000V range with 10V step (MIC-30)
 - Automatic measurement in sockets with the UNI-Schuko adapter (MIC-30) with possibility of configuring pairs of measured cables.
 - Continuous indication of insulation resistance or leakage current
 - Automatic discharge of capacitance of tested object after the insulation resistance measurement
 - Acoustic signaling of five-second periods to facilitate obtaining time characteristics
 - Measured test times T1, T2 I T3 to measure one or two absorption coefficients in the 1...600 sec. range (only MIC-30)
 - Indication of actual test voltage during the measurement
 - Protection against measuring live objects
 - Three-lead measurement

- ◆ **Continuity measurement of protective and equipotential conductors according to EN 61557-4 with the >200mA current**
- ◆ **Low-voltage circuit continuity and resistance measurement:**
 - Circuit resistance measurement (<1999) with the <15mA current
 - Quick sound signal if circuit resistance is below 30
- ◆ **Leakage current measurement (only MIC-30)**
- ◆ **Capacitance measurement during the R_{iso} measurement**
- ◆ **Measurement of alternating and direct voltages in the 0...600V range**
- ◆ **990 memory cells and wireless data transmission to a computer using Bluetooth (only MIC-30)**
- ◆ **Power supply: 4 AA disposable or rechargeable batteries, monitoring of power supply voltage.**
- ◆ **Meters conform to EN 61557**



WEB: www.austutilities.com.au
EMAIL: sales@austutilities.com.au

PHONE: 08 9406 3200



Sonel 1kV Insulation Tester

Insulation resistance measurement

Measuring range according to EN 61557-2 for $U_n=50V$: 50k Ω ...250,0M Ω

Range	Resolution	Accuracy
0,0...999,9k Ω	0,1k Ω	$\pm(3\% \text{ m.v.} + 8 \text{ digits})$ $[\pm(5\% \text{ m.v.} + 8 \text{ digits})]^*$
1,000...9,999M Ω	0,001M Ω	
10,0...99,99M Ω	0,01M Ω	
100,0...250,0M Ω	0,1M Ω	

*- for the WS-04 lead (MIC-30)

Measuring range according to EN 61557-2 for $U_n=100V$: 100k Ω ...500,0M Ω

Range	Resolution	Accuracy
0,0...999,9k Ω	0,1k Ω	$\pm(3\% \text{ m.v.} + 8 \text{ digits})$ $[\pm(5\% \text{ m.v.} + 8 \text{ digits})]^*$
1,000...9,999M Ω	0,001M Ω	
10,0...99,99M Ω	0,01M Ω	
100,0...500,0M Ω	0,1M Ω	

*- for the WS-04 lead (MIC-30)

Measuring range according to EN 61557-2 for $U_n=250V$: 250k Ω ...2,000G Ω

Range	Resolution	Accuracy
0,0...999,9k Ω	0,1k Ω	$\pm(3\% \text{ m.v.} + 8 \text{ digits})$ $[\pm(5\% \text{ m.v.} + 8 \text{ digits})]^*$
1,000...9,999M Ω	0,001M Ω	
10,0...99,99M Ω	0,01M Ω	
100,0...999,0M Ω	0,1M Ω	
1,000...2,000G Ω	0,001G Ω	

*- for the WS-04 lead (MIC-30)

Measuring range according to PN-EN 61557-2 for $U_n=500V$:

- 500k Ω ...5,00G Ω (MIC-10)
- 500k Ω ...20,00G Ω (MIC-30)

Range	Resolution	Accuracy	
0,0...999,9k Ω	0,1k Ω	$\pm(3\% \text{ m.v.} + 8 \text{ digits})$ $[\pm(5\% \text{ m.v.} + 8 \text{ digits})]^*$	
1,000...9,999M Ω	0,001M Ω		
10,00...99,99M Ω	0,01M Ω		
100,0...999,0M Ω	0,1M Ω		
1,000...5,000G Ω	0,001G Ω	$\pm(4\% \text{ m.v.} + 6 \text{ digits})$	MIC-10
1,000...9,999G Ω	0,001G Ω	$\pm(4\% \text{ m.v.} + 6 \text{ digits})$	MIC-30
10,00...20,00G Ω **	0,01G Ω	$[\pm(6\% \text{ m.v.} + 6 \text{ digits})]^*$	

*- for the WS-04 lead (MIC-30)

** - for the WS-04 lead - range to 10G Ω

Measuring range according to EN 61557-2 for $U_n=1000V$:

- 1000k Ω ...10,00G Ω (MIC-10)
- 1000k Ω ...100,00G Ω (MIC-30)

Range	Resolution	Accuracy	
0,0...999,9k Ω	0,1k Ω	$\pm(3\% \text{ m.v.} + 8 \text{ digits})$	
1,000...9,999M Ω	0,001M Ω		
10,00...99,99M Ω	0,01M Ω		
100,0...999,0M Ω	0,1M Ω		
1,000...5,000G Ω	0,001G Ω	$\pm(4\% \text{ m.v.} + 6 \text{ digits})$	MIC-10
5,00...10,00G Ω	0,01G Ω		MIC-10
1,000...9,999G Ω	0,001G Ω		MIC-30
10,00...99,99G Ω	0,01G Ω		MIC-30
100,0G Ω	0,1G Ω		MIC-30

Continuity measurement of protective and equipotential conductors with the 200mA current
Measuring range according to EN 61557-4: 0,10...1999 Ω

Range	Resolution	Accuracy
0,00...19,99 Ω	0,01 Ω	$\pm(2\% \text{ m.v.} + 3 \text{ digits})$
20,0...199,9 Ω	0,1 Ω	
2000...1999 Ω	1 Ω	$\pm(4\% \text{ m.v.} + 3 \text{ digits})$

- Voltage on open terminals: <8V
- Output current at $R < 2\Omega$: $I_{sc} > 200\text{mA}$; $I_{sc} > 200\text{mA}$
- Compensation of test leads' resistance
- MIC-30 - bidirectional current flow, average resistance value is displayed
- MMIC-10 - unidirectional current flow

Low-voltage and resistance measurement

Range	Resolution	Accuracy
0,0...199,9 Ω	0,1 Ω	$\pm(3\% \text{ m.v.} + 3 \text{ digits})$
200...1999 Ω	1 Ω	

- Voltage on open terminals: <8V
- Current for closed terminals 5mA < ISC < 15mA
- Sound signal and green LED on when measured resistance < 30 $\Omega \pm 50\%$
- Compensation of test leads' resistance,

Capacitance measurements

Range	Resolution	Accuracy
1...999nF	1nF	$\pm(5\% \text{ m.v.} + 5 \text{ digits})$
1,00...9,99 μF	0,01 μF	

- Capacitance value displayed during the R_{90} measurement
- For test voltages below 100V and measured resistance below 10M Ω , unspecified capacitance measurement error

Measurement of alternating and direct voltage

Range	Resolution	Accuracy
0,0...299,9V	0,1V	$\pm(2\% \text{ m.v.} + 6 \text{ digits})$
300...600V	1V	$\pm(2\% \text{ m.v.} + 2 \text{ digits})$

- Frequency range: 45...65Hz

Standard accessories:

- MIC-30 Test lead with banana plug; 1,2m; red
- MIC-30 Test lead with banana plug; 1,2m; blue
- MIC-30 Shielded test lead with banana plug; 1,2m; black
- MIC-30 "Crocodile" clip K02; blue
- MIC-10 Test lead with banana plug; 1,2m; black
- MIC-10 Test lead with banana plug; 1,2m; red
- MIC-10 "Crocodile" clip K01; black
- Pin probe with banana connector; black
- Pin probe with banana connector; red
- Carrying case M6
- Hanging straps
- Handle to suspend the meter
- Certificate calibration
- Battery set

WAPRZ1X2REBB
WAPRZ1X2BUBB
WAPRZ1X2BLBB
WAKROBU20K02
WAPRZ1X2BLBB
WAPRZ1X2REBB
WAKROBLK01
WASONBLOGB1
WASONREOGB1
WAFUTM6
WAPQZSE4
WAPQZUCH1

Additional accessories:

- Test lead with banana plug 5m; red
- Test lead with banana plug 5m; blue
- Shielded test lead with banana plug; 5m; black
- Test lead with banana plug 1,2m; blue
- "Crocodile" clip K02; red
- "Crocodile" clip K01; black
- "Crocodile" clip K02; blue
- Pin probe with banana connector; blue
- Adapter WS-04 with UNI-Schuko
- MIC-30 Software for creation of documentation from electrical measurements "SONEL Reports"

WAPRZ005REBB
WAPRZ005BUBB
WAPRZ005BLBB
WAPRZ1X2BUBB
WAKRORE20K02
WAKROBL20K01
WAKROBU20K02
WASONBLOGB1
WADAW04

WAPROSONPE4

Electric safety:

- type of insulation double, according to EN 61010-1 and IEC 61557
- measurement category IV 600V (III 1000V) according to EN 61010-1
- protection class acc. to EN 60529 Ip67

Other technical data:

- power supply 4 alkaline batteries or or battery package NI-MH
- weight ~0,6 kg
- dimensions 220 x 100 x 60 mm
- humidity 20%...90%



WEB: www.austutilities.com.au
EMAIL: sales@austutilities.com.au

PHONE: 08 9406 3200