

SHOTGUN/GRIPALL STICK



**CANVAS STORAGE BAGS
AVAILABLE ON REQUEST.**

BAG-RC4030292







BAG-RC4030293

FEATURES

The grip-all clampstick is a very versatile tool. It has a sliding hand grip mechanism that opens the hook to grasp a clamp and retracts it into the tool head. A thumb latch must be pressed to release the locked hand grip so it can open the hook.

Intended for multiple applications, the equipment is primarily used for installing live line and grounding clamps, as well as live line protective cover-up and test instruments etc.

PART NUMBER	Ø	TOTAL LENGTH	INSULATING LENGTH	MAX VOLTAGE	APPROX WEIGHT
RC403-0292	32	2.04	0.74	35	2.60
RC403-0293	32	2.65	1.30	138	3.10

OPEN	CLOSED	RETRACTED
Position to grip the grounding clamp eye-ring or other tools.	Hook grasps the grounding clamp eye ring, keeping it firm, but free to articulate, allowing torsion movements, inclusive in angle.	The hook is retracted into the head, keeping the grounding clamp connected to the stick, in the suitable position for its installation and removal.
		
		

REGULAR MODELS					
Cat. No.	Dimensions		Insul. Length (m)	Max. Voltage (kV)	Approx weight (kg)
	Ø (mm)	Total Length (m)			
RC403-0291	32	1.43	0.54	15	2.40
RC403-0292	32	2.04	0.74	35	2.60
RC403-0293	32	2.65	1.30	138	3.10
RC403-0294	32	3.26	1.86	230	3.50
RC403-0295	32	3.87	2.42	345	3.90

LIGHT MODELS					
Cat. No.	Dimensions		Insul. Length (m)	Max. Voltage (kV)	Approx weight (kg)
	Ø (mm)	Total Length (m)			
FLV08958-1	25	1.43	0.54	15	2.30
FLV08958-2	25	2.04	0.74	35	2.40
FLV08958-3	25	2.65	1.30	138	2.60
FLV08958-4	25	3.26	1.86	230	3.20
FLV08958-5	25	3.87	2.42	345	3.50