



Independent Earth Trailing Lead

Part Number: ETL20SS



SPECIFICATIONS

- ◆ 1000V Insulated Handle to eliminate the requirement to cover the spike with an insulating mat.
- ◆ 20m of flexible 1.0mm Cable 0.6/1kV.
- ◆ Dual colour cable to indicate damage Green/White.
- ◆ Adjustable drag system despite the use of tools.
- ◆ Option for direct connection via 4mm Banana plug.
- ◆ Brass Bushing for extra Low Resistance Connectivity
- ◆ Stackable Banana Plug for multiple connections at service end.
- ◆ Stainless steel construction.
- ◆ Auger for especially easy driving.

Part Number: ETL20SS-L

SPECIFICATIONS

- ◆ 1000V Insulated Handle to eliminate the requirement to cover the spike with an insulating mat.
- ◆ Extended 645mm earth stake for use in Loam Soil environments.
- ◆ 20m of flexible 1.0mm Cable 0.6/1kV.
- ◆ Dual colour cable to indicate damage Green/White.
- ◆ Adjustable drag system despite the use of tools.
- ◆ Option for direct connection via 4mm Banana plug.
- ◆ Brass Bushing for extra Low Resistance Connectivity
- ◆ Stackable Banana Plug for multiple connections at service end.
- ◆ Stainless steel construction.
- ◆ Auger for especially easy driving.



WEB: www.austutilities.com.au
EMAIL: sales@forcorp.com.au

PHONE: 08 9406 3200